Valenz

Trade name: Methanol

Current version : 3.0.1, issued: 28.02.2024

Replaced version: 3.0.0, issued: 30.01.2024

Region: GB

SECTION 1: Title and scope of exposure scenario (ES)

1.1 Title exposure scenario (ES)

ES7 Oil field drilling chemical - industrial use

1.2 Scope of exposure scenario (ES)

ES Type

Life cycle stage

Worker Exposure Scenario for substance/mixture Industrial end use

Product identifier

Trade name	Methanol
Substance name REACH registration no. CAS no. EC no.	methanol 01-2119433307-44 67-56-1 200-659-6

Use descriptors

Sector of use (SU)		
Category	Code	Use description
Main user group	SU3	Industrial uses
Environmental release ca	tegory (ERC)	
Category	Code	Use description
Environmental release category (ERC)	ERC7	Industrial use of substances in closed systems
Process category (PROC)		
Category	Code	Use description
Process category (PROC)	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises
	PROC5	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
	PROC8a	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
	PROC8b	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

SECTION 2: Operational conditions (OC) and risk management measures (RMM) controlling exposure towards environment and men

2.1 **Product characteristics**

State of aggregation	
liquid	
Reference temperature	25 °C
Dustiness	
Not relevant	
Vapour pressure	
Value	169.27 hPa
Reference temperature	25 °C

Current version : 3.0.1, issued: 28.02.2024

Replaced version: 3.0.0, issued: 30.01.2024

Region: GB

Other information

The efficiency of a risk management measure is a theoretical value. The efficiency describes to which extend (in percent) the calculated exposure can be diminished by applying a certain measure. If the described operational conditions and risk management measures are fulfilled by a downstream user, the efficiency as highlighted in the ES can be applied. A downstream user might check whether the efficiency of the LEV or general ventilation corresponds to his site.

For further instructions related to "Personal protective equipment" please refer to section 8 of the Safety Data Sheet.

2.2 Contributing scenario controlling environmental exposure

Affected environmental release category (ERC)				
Category	Code	Use description		
Environmental release	ERC7	Industrial use of substances in closed systems		
category (ERC)				

Risk management measures (RMM) controlling environmental exposure

Technical measures and efficiency of the risk managment measures (in exposure calculation model) No special measures are required.

Organisational measures

No special measures are required.

Measures related to wastewater treatment and efficiency of the risk managment measures (in exposure calculation model)

No special measures are required

Measures related to waste treatment

For further instructions related to waste management please refer to section 13 of the Safety Data Sheet.

Further measures ERC7

No special measures are required.

2.3 Contributing scenario controlling worker exposure

Affected process categor	y (PROC)	
Category	Code	Use description
Process category (PROC)	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises
	PROC5	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
	PROC8a	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
	PROC8b	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Operational conditions controlling worker exposure

Concentration of subst	tance					
	PROC4		PROC5		PROC8a	1
Value	≤ 100	%	≤ 5	%	≤ 5	%
	PROC8b					
Value	≤ 5	%				
Amounts used						
	PROC4		PROC5		PROC8a	1
	Not relevant		Not relevant		Not relev	vant

PROC4	PROC5	PROC8a
Not relevant	Not relevant	Not relevant
PROC8b		
Not relevant		

Current version : 3.0.1, issued: 28.02.2024

Replaced version: 3.0.0, issued: 30.01.2024

Region: GB

Use conditions								
	PROC4		PRO	C5		PR	OC8a	
Location of use	Indoor use		Indo	or use		Ind	oor use	
Duration of use	≤ 4	hours/day	≤	8	hours/day	S	8	hours/day
Frequency of use	≤ 240	days/year	≤	240	days/year	≤	240	days/year
	PROC8b							
Location of use	Indoor use							
Duration of use	≤ 8	hours/day						
Frequency of use	≤ 240	davs/vear						

Risk management measures (RMM) controlling worker exposure

Technical measures and efficiency of the risk managment measures (in exposure calculation model)				
PROC4	Measures	Handle only at a place with local exhaust system (or another appropriate exhaust).		
	Efficiency (%)	90		
PROC5	Measures	No special measures are required.		
PROC8a	Measures	No special measures are required.		
PROC8b	Measures	No special measures are required.		

Organisational measures

No special measures are required.

Personal protective equipment and efficiency of the risk managment measures (in exposure calculation model)

Hand protection		
PROC4	Measures	Wear suitable gloves tested to EN374.
	Efficiency (%)	80
PROC5	Measures	Wear suitable gloves tested to EN374.
	Efficiency (%)	80
PROC8a	Measures	Wear suitable gloves tested to EN374.
	Efficiency (%)	80
PROC8b	Measures	Wear suitable gloves tested to EN374.
	Efficiency (%)	80

SECTION 3: Exposure estimation and reference to sources

3.1 Advice

The Risk Characterization Ratio (RCR) is the quotient of predicted human/environmental exposure and the related DNEL/PNEC. Exposure is calculated based on exposure models as stated below. If RCR \leq 1 a use is considered as safe under operational conditions and risk management measures as specified in the exposure szenario.

For DNEL/PNEC values please refer to section 8 of the safety data sheet.

3.2 Exposure estimation - Environment

Affected environmental release category (ERC)			
Category	Code	Use description	
Environmental release category (ERC)	ERC7	Industrial use of substances in closed systems	
Used exposure estimation model for calculation of environmental exposure			

Used exposure estimation model As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.



Current version : 3.0.1, issued: 28.02.2024

Replaced version: 3.0.0, issued: 30.01.2024

Region: GB

3.3 Exposure estimation - Worker

Affected process category (PROC)			
Category	Code	Use description	
Process category (PROC)	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	
	PROC5	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)	
	PROC8a	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities	
	PROC8b	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities	

Used exposure estimation modelfor calculation of worker exposureUsed exposure estimation modelEasyTRA Version 3.0Link to exposure estimation toolEASY TRA: http://www.easytra.de

Risk characterisation ratio (RCR)				
	Exposure estimation	inhalative	dermal	total
PROC4	Long-term systemic	0.031	0.020	0.051
	Short-term systemic	0.205	0.020	0.225
PROC5	Long-term systemic	0.064	0.003	0.067
	Short-term systemic	0.128	0.003	0.131
PROC8a	Long-term systemic	0.064	0.003	0.067
	Short-term systemic	0.128	0.003	0.131
PROC8b	Long-term systemic	0.038	0.003	0.041
	Short-term systemic	0.077	0.003	0.080

SECTION 4: Guidance to DU to evaluate whether he works inside the boundaries set by the ES

4.1 Recommendations and advice

Recommendations and general advice

- For additional instructions relating to adaptation of conditions of use in view of a scaling, pls. see the "ECHA Guidance for downstream users" http://echa.europa.eu/regulations/reach/downstream-users If a downstream user uses the substance/preparation differently than stated in the ES (different operational conditions and/or risk management measures), he has the possibility to vary certain parameters of the exposure assessment. With the help of easy calculations he can check whether he still operates under safe circumstances. This process is called Scaling.

Scaling advice

Type of ventilation

If the type of ventilation at the use site of a downstream user (DU) differs from the instructions in the ES, a linear correlation between the RCR (Inhalation) and the type of ventilation exists. Following scaling factors (f) apply: General ventilation (< 3 air changes per hour) =1; good general ventilation (3 to 5 air changes per hour, corresponds to outdoor use) = 0,7; enhanced general ventilation (> 5 air changes per hour) = 0,3.

RCR (DU) = f(DU) * RCR (as stated in ES) / f (type of ventilation stated in ES)

In the same manner a scaling for the efficiency of the local extract ventilation (LEV) can by applied.

Duration of use

If the duration of the use by a worker at a downstream user (DU) site differs from the instructions in the ES, a linear correlation between the RCR (Inhalation) and the duration of use exist. Following scaling factors (f) apply: duration > 4 hours/day = 1; duration: 1-4 hours/day = 0,6; duration: 15 min/day – 1 hour/day = 0,2; duration < 15 min/day = 0,1. RCR (DU) = f(DU) * RCR (as stated in ES) / f (duration in ES)

Concentration of the substance in the product

If the downstream user (DU) uses the substance in a different concentration than the one stated in the ES, a linear correlation between the RCR (Inhalation)and the RCR (dermal) and the concentration exists. Following scaling factors (f) apply: Concentration >25% =1; concentration >= 5% = 0,6; concentration >= 1% = 0,2; concentration < 1% = 0,1. RCR (DU) = f(DU) * RCR (as stated in ES) / f (concentration in ES).



Current version : 3.0.1, issued: 28.02.2024

Replaced version: 3.0.0, issued: 30.01.2024

Region: GB

4.2 Exposure estimation - Environment

Used exposure estimation model for calculation of environmental exposure			
Used exposure estimation model	sed exposure estimation model As no environmental hazard was identified no environmental-related exposure		
	assessment and risk characterization was performed.		

4.3 Exposure estimation - Worker

Used exposure estimation model for calculation of worker exposure			
Used exposure estimation model	EasyTRA Version 3.0		
Link to exposure estimation tool	EASY TRA: http://www.easytra.de		